SERENITY TECHNICAL DATASHEET

LIFE TIME GUARANTEE RESIDENTIAL | BEST LOC® | NO BEVELS | SILENT FLOOR

BERRYALLOC®
THE WORLD IS OUR HOME

LAMINATE

Product Description

• Dimensions	1285 L x 204 W x 8 TH
• Packaging	Box: 8 boards - 2.10 m² (15.52 kg) Pallet : 56 boxes - 117.44 m² (890 kg)
• Density (average)	930 kg/m³
• Composition	
› Surface layer	PU Vinyl
› Wear layer	0.55 mm
› Substrate	Moisture-resistant High Density Fibreboard, HDF
› Backing	Direct Laminated Paper. Paper impregnated with melamine resin
• Features	Matlook
• Installation	Best Loc: glue-free mechanical locking system produced under license of Välinge Innovation AB, Flooring Industries Ltd and Faus Group Inc
• Installation instruction	see box inlay or www.berryalloc.com

Classification

• According E685	class 23/33

Characteristics	Method	Result
Thickness swelling	EN13329	≤ 18%
Effect of a castor chair	EN425	No change in appearance or damage,type W
Fire resistance	EN13501-1	B_{fl}-S1
Formaldehyde	EN717-1	E1
Slipperiness	DIN 51130	R10
	EN13983	DS
Impact resistance	EN433	‹ 0,10 mm
Antistatic	DIN EN 1815	yes
Light fastness	ISO 105-B02	≥ 6
Chemical resistance	EN 423	OK

Other technical data

- Sustainability of forests: PEFC certified (07-31-229)
- Labelling according to French VOC emission regulation: A
- Floor heating: see specific instructions at www.berryalloc.com
- Thermal resistance in combination with underlay Excellence Endurance: 0,10 m² K/W

Warranty and maintenance

• Residential warranty	Lifetime
• Commercial warranty	6 years
• Warranty conditions	see www.berryalloc.com
• Care and maintenance	see www.berryalloc.com